


Kwikset

Signature Series

Specifications:

Door Prep	Cross Bore 2-1/8". Edge Bore 1". Latch Face 1" x 2-1/4".
Backset	Adjustable to 2-3/8" or 2-3/4". UL 2-3/4" standard 2-3/8" optional
Door Thickness	1-3/8" – 1-3/4" doors standard. 2-1/4" doors optional on 720 and 740 functions only.
Cylinder	SmartKey™ Pin & Tumbler
Faceplates	1" x 2-1/4". Specify round corner, square corner or drive-in.
Strikes	2-1/4" full lip. Specify round corner or square corner. Other options available.
Bolt	1/2" throw.
Door Handing	Reversible for both left and right handed doors.
ANSI/BHMA	Grades 2 Certified.
ADA	N/A
UL	Meets UL 3 hour fire rating for 725, 735, 745, 746, 755. Optional UL 1/3 hour fire rating for all functions.

Dimensions:



Design	A	B	C
Hancock®	2 5/8"	2 1/2"	2 3/8"



Hancock knob in Antique Brass

Functions:

Entry 740H		Both knobs locked or unlocked by key outside or turnbutton inside.
Bed & Bath 730H		Both knobs locked or unlocked by turnbutton inside. Unlocked by emergency key outside.
Hall & Closet 720H		Both knobs always free.
Inactive 788H		For doors where only a pull is required. No operation.
***Additional functions available		

Finishes:



Kwikset

19701 DaVinci, Lake Forest, CA 92610 • Kwikset.com • 1-800-327-5625
©2020 Spectrum Brands, Inc. Kwikset is a trademark of Spectrum Brands, Inc. Lake Forest, CA 92610 • 433737-05/2020