






# TYLO®

## Specifications:

<b>Door Prep</b>	Cross Bore 2-1/8". Edge Bore 1".
<b>Backset</b>	Adjustable 2-3/8" or 2-3/4".
<b>Door Thickness</b>	1-3/8" to 1-3/4" standard, 2 1/4" doors optional on 200 and 400 functions only
<b>Cylinder</b>	SmartKey or Traditional 5-pin Pin & Tumbler
<b>Faceplates</b>	1" x 2-1/4" Specify round corner or square corner. Also available as drive-in latch.
<b>Strikes</b>	2-1/4" full lip. Specify round corner or square corner. Other options available.
<b>Bolt</b>	1/2" throw.
<b>Door Handling</b>	Reversible for right or left hand doors.
<b>ANSI/BHMA</b>	A156.2 Grade 3 (all functions except 488)

## Functions:

	<b>200 Passage/Hall/Closet:</b> Both knobs always free.
	<b>300 Privacy/Bed/Bath:</b> Both knobs locked or unlocked by turnbutton inside. Unlocked by emergency key outside.
	<b>400 Keyed Entry:</b> Both knobs locked or unlocked by key outside or turnbutton inside.
	<b>401 Keyed Entry, Free Interior:</b> Outside locked or unlocked by key outside or turn button inside. Inside always free.
	<b>488 Half Dummy Trim, Surface Mounted:</b> For doors where only a pull is required. No operation.

\*See price book for complete listing



## EASILY RE-KEY IN THREE EASY STEPS




Insert functioning key and turn 1/4 turn clockwise.

Insert and remove the SmartKey learn tool. Remove functioning key.

Insert new key and turn 1/2 turn counter-clockwise. Your lock is now re-keyed!

## Dimensions:

	Design	A	B	C
	Tylo®	2 5/8"	2 19/32"	1 7/8"



## Finishes:



Polished Brass (3)



Antique Brass (5)



NEW Satin Nickel (15)



Polished Chrome (26)



Satin Chrome (26D)