


PEMBROKE LEVER

Evoking a sense of antiquity, the Pembroke delivers style with the guarantee of solid craftsmanship.

- Featuring SmartKey Security[™]
- ANSI BHMA Grade 2 Certified
- Certified Security

Signature Series







Pembroke[™] Lever in Venetian Bronze



Specifications

Door Prep	Cross Bore 2-1/8". Edge bore 1".		
Backset	Adjustable $2^{-3}/8$ " or $2^{-3}/4$ ". UL functions $2^{-3}/4$ " standard or $2^{-3}/8$ " optional.		
Door Thickness	1- ³ /8" - 1- ³ /4" Doors standard.		
Cylinder	SmartKey Security [™] or Pin & Tumbler 1" x 2-1/4" Specify round corner, square corner or drive-in.		
Faceplates			
Strikes	2-1/4" Full lip. Specify round corner or square corner. Other options available.		
Bolt	¹/₂" Throw		
ANSI/BHMA	Grade 2 Certified		
ADA	200 and 488 functions satisfies section 4.13.9 ADA requirements.		
UL	Meets 3-hour fire rating for all UL specific functions.		

Functions



Passage/Hall/Closet: Both levers always free



Privacy/Bed/Bath: Both levers locked or unlocked by turnbutton inside. Outside lever unlocked by emergency key



Keyed Entry Lever: Both sides locked or unlocked by key outside or turnbutton inside



Half Dummy Trim, Surface Mounted:

For doors where only a pull is required. No operation




Interior Pack:

Outside handleset. Inside lever.

*See price book for complete listing



Dimensions



Design	Α	В	С	C (Keyed)
Pembroke™	2 5/8"	4 7/32"	2 23/32"	2 23/32"



Pembroke[™] Lever in Polished Chrome



Pembroke[™] Lever in Matte Black

WARRANTY

Finishes



Venetian Bronze 11P



Satin Nickel 15



Antique Nickel 15A



Polished Chrome 26



Matte Black 514