

Introducing TYLO[®]

in Satin Nickel

Featuring  **SMARTKEY**
RE-KEY TECHNOLOGY



Features SmartKey[®] Re-key Technology
with BumpGuard[™] Protection
ANSI/BHMA Grade 3 Certified Quality & Security
Lifetime Mechanical Warranty



Kwikset

TYLO[®]

Specifications:

Door Prep	Cross Bore 2-1/8". Edge Bore 1".
Backset	Adjustable 2-3/8" or 2-3/4".
Door Thickness	1-3/8" to 1-3/4" standard, 2 1/4" doors optional on 200 and 400 functions only
Cylinder	SmartKey or Traditional 5-pin Pin & Tumbler
Faceplates	1" x 2-1/4" Specify round corner or square corner. Also available as drive-in latch.
Strikes	2-1/4" full lip. Specify round corner or square corner. Other options available.
Bolt	1/2" throw.
Door Handing	Reversible for right or left hand doors.
ANSI/BHMA	A156.2 Grade 3 (all functions except 488)

Functions:

	200 Passage/Hall/Closet: Both knobs always free.
	300 Privacy/Bed/Bath: Both knobs locked or unlocked by turnbutton inside. Unlocked by emergency key outside.
	400 Keyed Entry: Both knobs locked or unlocked by key outside or turnbutton inside.
	401 Keyed Entry, Free Interior: Outside locked or unlocked by key outside or turn button inside. Inside always free.
	488 Half Dummy Trim, Surface Mounted: For doors where only a pull is required. No operation.

*See price book for complete listing



EASILY RE-KEY IN THREE EASY STEPS




Insert functioning key and turn 1/4 turn clockwise.

Insert and remove the SmartKey learn tool. Remove functioning key.

Insert new key and turn 1/2 turn counter-clockwise. Your lock is now re-keyed!

Dimensions:


Design	A	B	C
Tylo [®]	2 5/8"	2 19/32"	1 7/8"



Finishes:



Polished Brass (3)



Antique Brass (5)



NEW
Satin Nickel (15)



Polished Chrome (26)



Satin Chrome (26D)